


# Bennic Capacitors (Electrolytic & Polypropylene)

## Metallized Polypropylene Capacitors, XPP Series, 160VAC/250VDC

Tolerance Range : +/- 5%  
 Dissipation Factor : Maximum 0.07% @ 1KHz  
 Operating Temp. : -40°C to +105°C  
 Capacitance Drift : Maximum 2% cycled through the operating temp. range  
 Insulating Resist. : Min. 10,000 Mega-Ohm X rated caps (mfd) at 25°C  
 Life Test : 150% of rated working voltage at 105°C for 1,000 hours  
 Lead Length : 40 mm minimum  
 Color : Black tape, Yellow body, White wording



Value mfd	D / L mm	Price Each	Value mfd	D / L mm	Price Each
0.1	6 / 16	\$0.45	4.7	19 / 36	\$2.60
0.47	8 / 24	\$0.65	5.6	17 / 45	\$2.85
1.0	10 / 31	\$0.80	6.8	18 / 45	\$3.05
1.5	12 / 31	\$1.00	8.2	20 / 46	\$4.05
2.2	14 / 31	\$1.40	10	23 / 46	\$4.50
2.7	15 / 31	\$1.55	12	22 / 55	\$4.90
3.3	16 / 35	\$1.90	16	24 / 55	\$6.30
3.9	16 / 35	\$2.20			

## BI-POLAR ELECTROLYTIC CAPACITORS, 100WV

Tolerance Range : +/- 10% @ 1KHz  
 Leakage : Maximum 0.04 CV + 3 µA After Charge 5 Minutes  
 Temp. Range : -40°C to +85°C  
 Surge Volt : 125 for 100WV  
 Lead Length : 40 mm minimum  
 Max D.F. : Maximum 5% @ 1KHz Values 12mfd to 150mfd  
 Maximum 10% @ 1KHz Values 165mfd to 1000mfd  
 Color : Blue



Value mfd	D.F.	D / L mm	Price Each	Value mfd	D.F.	D / L mm	Price Each
12	5%	12 / 31	\$0.85	140	5%	22 / 45	\$3.50
18	5%	12 / 31	\$1.00	150	5%	22 / 45	\$3.70
22	5%	12 / 31	\$1.10	165	10%	16 / 42	\$3.30
31	5%	16 / 34	\$1.30	180	10%	16 / 42	\$3.60
40	5%	16 / 34	\$1.50	200	10%	16 / 42	\$3.65
50	5%	16 / 34	\$1.70	250	10%	18 / 42	\$4.50
65	5%	16 / 34	\$1.90	280	10%	18 / 45	\$5.00
80	5%	16 / 42	\$2.20	330	10%	22 / 45	\$5.40
100	5%	18 / 42	\$2.40	500	10%	25 / 51	\$7.35
125	5%	22 / 45	\$2.95	1000	10%	25 / 60	\$10.25

## Carli Metallized Polyester Film Capacitors (Mylar)

Carli Metallized Polyester Film Capacitors (Mylar)				
Value µfd	Description	Ø mm	L mm	Price Each
1.0	Mylar 10% 150 volt	8	19	\$0.60
2.7	Mylar 10% 150 volt	10	31	1.00
3.3	Mylar 10% 150 volt	11	25	1.05
3.9	Mylar 10% 150 volt	12	31	1.15
4.7	Mylar 10% 150 volt	13	31	1.25
6.0	Mylar 10% 150 volt	14	31	1.50
6.8	Mylar 10% 150 volt	14	31	1.70
8.0	Mylar 10% 150 volt	16	31	1.95
10.0	Mylar 10% 150 volt	16	31	2.30
12.0	Mylar 10% 150 volt	20	31	2.75

Carli Metallized Polyester Film Capacitors (Mylar)				
Value µfd	Description	Ø mm	L mm	Price Each
15.0	Mylar 10% 150 volt	23	31	3.40
20.0	Mylar 10% 150 volt	21	46	5.00

